
Compound-eye LED White Light Illuminator









Product Overview

• Delivers high power white light for night time illumination, it's significantly improves monitor effects of night vision camera.

• Adopted with Compound-eye LED lens, the product performs more smoothly and evenly light spot radiation.

- Excellent color rendering index, truly reserve object colors.
- Innovating high-efficiency driver provides a zero maintenance product.
- · Good heat dissipation and IP66 waterproof aluminum housing ensures

efficient, reliable and continuous operation of LED.

Product Features

- Outstanding illumination performance
- Auto day/night switch, customize to be synchronized with camera
- To improve performance of night vision camera and enhance image quality
- IP66 waterproof, indoor/outdoor use
- Low temperature operate
- Lifetime 50,000 hours
- Energy saving technology
- 2 year warranty

Wide Application

Parking lot, Residence Community, Building, Road, Garden, Field

Viewing picture at night



With white light

Without white light

Compound-eye LED White Light Illuminator

Technical Specification

Drawing

LED type: 15pieces high power white light LED Luminous flux: 1800lm Color temperature: 5000K-6500K Beam angle: 30 to 60° Beam distance: 60 to 40m Bracket: wall mount bracket Working voltage: 85-265V AC Power consumption: 18W Day/night switch: automatic Working temperatures: -30 to 50°C Protection level: IP66 Color: beige Panel: tempered glass panel Housing: aluminum die-casting housing N.W: 1.2KG G.W: 1.5KG Dimension: L181*H131*W72mm Packing dimension: L210*H180*W100mm


Model for Selection

Model	Beam angle	Viewing distance
S-SG15A-30-A-W	30°	60m
S-SG15A-45-A-W	45°	50m
S-SG15A-60-A-W	60°	40m


*Viewing distance is tested by Sony 1/3 CCD Camera with 0.01LUX.

*To achieve the distance needed, please pay attention to your camera specification and lens before purchase. It is normal phenomenon that distance may vary due to different cameras and lens.

181



Unit: mm







-

131